## **Assembly Instructions For Traditional Table With 2 Benches**

**Tools Needed:** 

Hammer For Light Tapping 7/16" Wrench or Socket Drill & Bit Set (Optional)

Parts List:

Table Top (1) Bench Tops (2) Table Legs (2) Bench Legs (4)

Table Braces-long (2) Bench Braces-short (4) Hardware:

1/4" x 2-3/4" Bolts (12) 1/4" x 2-1/2" Lag Screws (12) Allen Wrench (1)

)

- Step 1 Lay out and identify all the parts and pieces.
- Step 2 Lay the top upside down on a clean surface. Take the legs and set them upside down on the table inside the 2x2. Align the predrilled holes in the table legs with the threaded inserts in the 2x2. Insert two 2-3/4" bolts through the leg & turn into the inserts. Tighten with the Allen wrench.
- Attach the braces to the table by placing one end of the brace on the bottom of the table and the other end against the horizontal 2x4 of the table leg. Insert a 2-1/2" lag screw into the predrilled holes in the braces. Tap with the hammer to start them in then tighten with the 7/16" wrench or socket. Make sure you attach the braces to a solid piece of wood & not the crack between the boards. (The table and the legs do not have predrilled holes to attach the braces as the lag screws are self drilling and will not crack the table or the legs. The lag screws will not pull tight with predrilled holes). Do not over tighten the lag screws.
- (For benches only) Set your table upright and lay the benches face down on a clean surface. Now attach the bench legs to the inside of the 2x2. Align the predrilled holes in the bench legs with the threaded inserts in the 2x2. Insert two 2-3/4" bolts through the leg & turn into the inserts. Tighten with the Allen wrench. (Make sure you have the horizontal brace on the bench leg turned toward the outside of the bench). Now attach the braces to the bench in the same manner you attached the table braces. Make sure you turn the lag screws into one of the seat boards and not the crack between the boards. Do not over tighten the lag screws.

If you ordered the table only skip Step 4.

